



DATENBLATT

Opticon NLV-1001

Was können wir für Sie tun?

Gerne helfen wir Ihnen bei der Suche Ihrer passgenauen Lösung für die Kennzeichnung und Identifikation. Ob Standardlösung oder die Planung und Entwicklung spezifischer Systeme – Schneider-Kennzeichnung ist Ihr kompetenter Partner.

SERVICE HOTLINE: +49 (0) 711 9539490

www.schneider-kennzeichnung.de

NLV-1001

Laser scanner

The NLV-1001, a low-cost fixed mount scanner, quickly and efficiently scans 1D barcodes for light industrial or retail applications. This fixed mount scanner uses a bi-directional scanning approach to achieve a scan rate of 100 sps.



Highlights

- Rapidly scans and decodes a wide variety of 1D barcodes
- Bi-directional scanning at 100 scans/second
- Complete unit with integrated decoder
- Durable – survives 0.75 m drop to concrete
- IP43 rating against dust and moisture
- Compact size and weight: 30 x 20 x 43.3 mm (WxHxD) and 30 grams
- Trigger modes: manual test button, multiple read, auto-trigger, hardware and software trigger
- Communication interface: USB or RS232
- Backed by a two year warranty



NLV-1001

Product Specifications

Operating indicators

Visual: 1 LED (red/green/orange)

Non-visual: Buzzer

Communication

RS232: DB9 connector with external power supply, without connector

USB: Ver. 1.1, HID/VCP, USB-A connector

Power

Voltage requirement: 5V $\pm$ 10%

Current consumption: 85 mA (typical use), max. 150 mA

Barcode scanner optics

Light source: 650 nm visible laser diode

Scan method: Bi-directional scanning

Scan rate: 100 scans / second

Trigger mode: Manual, multiple read, auto-trigger, serial software trigger

Reading pitch angle: $\pm$ 35°

Reading skew angle: -50 to 8°, 8 to +50°

Reading tilt angle: $\pm$ 20°

Curvature: $R \geq 15$ mm (EAN8), $R \geq 20$ mm (EAN13)

Min. resolution at pcs 0.9: 0.127 mm / 5 mil

Min. pcs value: 0.45

Depth of field at code 39:

60 - 100 mm (0.127 mm) / 2.36 - 3.94 in (5 mil)

50 - 130 mm (0.15 mm) / 1.97 - 5.12 in (6 mil)

50 - 240 mm (0.25 mm) / 1.97 - 9.45 in (10 mil)

50 - 400 mm (0.5 mm) / 1.97 - 15.75 in (20 mil)

70 - 630 mm (1.0 mm) / 2.76 - 24.80 in (39 mil)

Supported symbologies

Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 Databar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN, Matrix 2of5, MSI/

Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey

Postal code: Chinese Post, Korean Postal Authority code

2D code: Composite codes, MicroPDF417, PDF417

Durability

Temperature in operation: -10 to 45 °C / 14 to 113 °F

Temperature in storage: -20 to 60 °C / -4 to 140 °F

Humidity in operation: 20 - 85% (non-condensing)

Humidity in storage: 20 - 90% (non-condensing)

Ambient light immunity: Fluorescent 3,000 lx max, Sunlight 50,000 lx max, Incandescent 3,000 lx max

Antistatic electricity: 10 kV (non-destructive)

Drop test: 0.75 m / 2.5 ft drop onto concrete surface

Protection rate: IP67

Physical

Dimensions (WxHxD): 30 x 20 x 43.3 mm / 1.18 x 0.79 x 1.70 in

Weight: Ca. 30 g / 1.1 oz (excl. cable)

Case: ABS, Black

Regulatory & Safety

CE, FCC, VCCI, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II, IEC/EN60950-1, EN55022, EN55024

Items

Sold separately: Power supply 100-240V/0.5A, 50/60 Hz, 5V/2A (for RS232)

Models

Interface: RS232, USB